Recovering heat

VENTILATION UNIT

Deekax Talteri DIVK-C 91 C
Deekax Talteri DIVK-C 96 C

LVI 7903471 (R)
LVI 7903472 (L)
LVI 7903473 (R)
LVI 7903474 (L)

MADE IN FINLAND ®



- Demand-controlled ventilation
- Heat recovery with countercurrent transfer
- Annual efficiency over 80 %
- Demand-controlled filtration and heating for supply air
- Speed adjustment by EC-cooker hood
- Direct current fans
- Kitchen bypass
- The unit is equipped with noise insulated, white powder coated casing



DS-600 EC



DSA-900 EC



ULTRA PG EC



ULTRA PC EC

DEEKAX ®

Deekax Talteri DIVK-C91 C ja C96 C




MACHINE PARTS AND TECHNICAL DATA

- Exhaust air..... ø 125 mm
- Outdoor air ..... ø 125 mm
- Extract air..... ø 125 mm
- Supply air ..... ø 125 mm
- Kitchen bypass..... ø 125 mm
- Maintenance switch
- Supply fan ..... EC 118 W / 166 W
- Exhaust fan ..... EC 118 W / 166 W
- Countercurrent heat exchanger
- Afterheating Electric... 500 W
- Pre-heating ..... 1000 W
- Exhaust air filter ISO Coarse >75%
- Supply air filter ISO ePM1
- Exhaust of condensing water
- Summer bypass, automatic


MOUNTING ACCESSORIES:

7903421 Ceiling mounting plate
7903295 Wall mounting kit


DIVK-C91 C



DIVK-C96 C



Dimensions: Height 495 mm, Width 558 mm,
Depth 520 mm, Weight 51 kg



We are constantly developing our products and we reserve the right to make changes

Deekax Air Oy
Patruunapolku 4
79100 Leppävirta
Puh. +358 207 912550

www.deekaxair.fi

deekax@deekaxair.fi

TEHTY SUOMESSA
MADE IN FINLAND